

INC


INC 35



DIFF.
VETRO

IP 67 IK 10 20J xx9 CE UK CA 500 KG MAX 65° MAX

LED	W	LM	REAL LM	COL.	CODE **	* OPTIC	* LED COLOUR
2	180	120	500mA - 4,8V		LL132000□□	S 14°	N 4000K
					LL132001□□	M 29°	3 3000K, Im -5%
					LL132002□□	L 46°	2 2700K, Im -5%
2	180	120	12/24V		LL132003□□		
					LL132004□□		
					LL132005□□		



Versione ghiera tonda, possibile scelta di 3 differenti ottiche.
Temperatura massima rilevata sul vetro 65°C.

Version with round retaining ring, choice of 3 different optics.
Max. temperature measured on the glass 65°C.

Version avec virole ronde, choix possible de 3 optiques différentes. Température relevée sur le verre 65° C maxi.


INC 50



DIFF.
VETRO

IP 67 IK 10 20J xx9 CE UK CA 500 KG MAX 65° MAX

LED	W	LM	REAL LM	COL.	CODE **	* OPTIC	* LED COLOUR
6,5	650	418	500mA - 14V		LL132006□□	S 13°	N 4000K
					LL132007□□	M 24°	3 3000K, Im -5%
					LL132008□□	L 53°	2 2700K, Im -5%
6,5	650	418	24V		LL132009□□		
					LL132010□□		
					LL132011□□		



Versione ghiera tonda, possibile scelta di 3 differenti ottiche.
Temperatura massima rilevata sul vetro 65°C.

Version with round retaining ring, choice of 3 different optics.
Max. temperature measured on the glass 65°C.

Version avec virole ronde, choix possible de 3 optiques différentes. Température relevée sur le verre 65° C maxi.



Finishing

Inox satinato
Satin grey
Inox satiné

Grigio antracite RAL 7021
Grey anthracite RAL 7021
Gris anthracite RAL 7021

Bianco RAL 9010
White RAL 9010
Blanc RAL 9010

* Led colour

N 4000K
3 3000K, Im -5%
2 2700K, Im -5%

Completa il codice
sostituendo al quadrato rosso la lettera o il numero corrispondente alla temperatura colore scelta.

Complete the code
by replacing the red box with the letter or number corresponding to the selected colour temperature.

Compléter le code
en remplaçant le carré rouge par la lettre ou le numéro correspondant à la sélection de température couleur.

⊗ Alimentatore escluso

Driver not included
Alimentation non incluse