











Color: Black Anodized Alluminum



Available colours:

Grey Anodized Alluminum	
Black Anodized Alluminum	
Green Anodized Alluminum	
Brown Anodized Alluminum	

Technical information:

Type of product:	Ground recess
Diffuser type:	Serigraphed glass
Lamp type:	LED
Energy performance class:	A++
Colour temperature:	N 4000K 3 3000K, lm -5% 2 2700K, lm -5%
Optics:	D Diff. S 25° M 40° L 65°
CRI:	>80
Photobiological risk:	RG0
Watt:	6
Lumen:	700
Real Lumen:	568
Power supply:	 220-240 V
Insulation class:	 CL.I
Type of protection:	IP 66
Resistance to breakage:	IK 07 2J xx5
Standards and Marks of Conformity:	
Pieces per package:	4

Suitable for ground installation.

Product description:

Suitable for ground installation and for outdoor use. Body made of EN-6026 anodized aluminum; highly resistant to oxidation due to anodizing treatment. Heat tempered and silk-screen printed glass. Inaccessible device, provided with 1 m prewired power cable HORN-F with epoxy resin treatment. A4 or AISI 316L stainless steel nuts and bolts. Phase cut dimmable. LED AC Direct. **LED 4000K (N), 3000K (3) or 2700K (2).** LED AC Direct. No risk of photobiological damage, RG0 group (EN62471).

Ago Garden

LL126001 □ □

LOMBARDO

