



Technical information:

Installation:	Ground
Material:	Aluminium
Finish:	Black Anodized Aluminium
Treatment:	Anodization
Diffuser type:	Serigraphed glass
Optics:	65°
Lamp type:	LED
Energy performance class:	F
Colour temperature:	3000K
CRI:	>80
LB Factor:	L80B50 - 50.000h
Photobiological risk:	RG1
Power consumption (Watt):	6
Lumen:	700
Real Lumen:	568
Power supply:	✓ integrated
LED:	AC DIRECT
Insulation class:	⊕ CL.I
Type of protection:	IP 66
Resistance to breakage:	IK 07 2J xx5
Standards and Marks of Conformity:	CE UK CA
Dimming	Phase cut

AC-Direct version cable: 0.8m H05RN-F 3x1. Cable 24V version: 0.8m H05RN-F 2x0.75. For the purchase of the product with a longer cable, we recommend the **Standard cable Ago Garden, Ago Wall, Ago Garden Power, Ago Wall Power** or the **Anti-rising damp cable Ago Garden, Ago Wall, Ago Garden Power, Ago Wall Power**



Ago Garden

LL126001L3

Lombardo.




Lombardo S.r.l.

Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - T 0039 035 939 411 - E info@lombardo.it

lombardo.it

Lighting simulation:



ago_garden_optic_l