



Color: Green Anodized Alluminum



### Available colours:

|                          |                                     |
|--------------------------|-------------------------------------|
| Grey Anodized Alluminum  | <input type="checkbox"/>            |
| Black Anodized Alluminum | <input type="checkbox"/>            |
| Green Anodized Alluminum | <input checked="" type="checkbox"/> |
| Brown Anodized Alluminum | <input type="checkbox"/>            |

### Technical information:

|                                    |   |
|------------------------------------|---|
| Type of product:                   | Ground recess   |
| Diffuser type:                     | Serigraphed glass   |
| Lamp type:                         | LED   |
| Energy performance class:          | A++   |
| Colour temperature:                | <input checked="" type="checkbox"/> 4000K<br><input checked="" type="checkbox"/> 3000K, lm -5%<br><input checked="" type="checkbox"/> 2700K, lm -5% |
| Optics:                            | <input type="checkbox"/> Diff.<br><input type="checkbox"/> 25°<br><input type="checkbox"/> 40°<br><input type="checkbox"/> 65°                      |
| CRI:                               | >80   |
| Photobiological risk:              | RG0   |
| Watt:                              | 6   |
| Lumen:                             | 700   |
| Real Lumen:                        | 568   |
| Power supply:                      | <input checked="" type="checkbox"/> 220-240 V   |
| Insulation class:                  | <input checked="" type="checkbox"/> CL.I  |
| Type of protection:                | IP 66   |
| Resistance to breakage:            | IK 07 2J xx5  |
| Standards and Marks of Conformity: | CE  |
| Pieces per package:                | 4   |

Suitable for ground installation.

### Product description:

Suitable for ground installation and for outdoor use. Body made of EN-6026 anodized aluminum; highly resistant to oxidation due to anodizing treatment. Heat tempered and silk-screen printed glass. Inaccessible device, provided with 1 m prewired power cable HORN-F with epoxy resin treatment. A4 or AISI 316L stainless steel nuts and bolts. Phase cut dimmable. LED AC Direct. LED 4000K (N), 3000K (3) or 2700K (2). LED AC Direct. No risk of photobiological damage, RG0 group (EN62471).

# Ago Garden

LL126002 ◻ ◻

LOMBARDO

