



### Technical information:

|                                    |                          |
|------------------------------------|--------------------------|
| Installation:                      | Ground                   |
| Material:                          | Aluminium                |
| Finish:                            | Green Anodized Aluminium |
| Treatment:                         | Anodization              |
| Diffuser type:                     | Serigraphed glass        |
| Optics:                            | 40°                      |
| Lamp type:                         | LED                      |
| Energy performance class:          | F                        |
| Colour temperature:                | 2700K                    |
| CRI:                               | >80                      |
| LB Factor:                         | L80B50 - 50.000h         |
| Photobiological risk:              | RG0                      |
| Power consumption (Watt):          | 6                        |
| Lumen:                             | 700                      |
| Real Lumen:                        | 568                      |
| Power supply:                      | ✓ integrated             |
| LED:                               | AC DIRECT                |
| Insulation class:                  | ⊕ CL.I                   |
| Type of protection:                | <b>IP 66</b>             |
| Resistance to breakage:            | <b>IK 07 2J xx5</b>      |
| Standards and Marks of Conformity: | CE UK ENEC               |
| Dimming                            | Phase cut                |

AC-Direct version cable: 0.8m H05RN-F 3x1. Cable 24V version: 0.8m H05RN-F 2x0.75.



# Ago Garden

LL126002M2

**Lombardo.**



### Lighting simulation:



ago\_garden\_optic\_m