
Clic Wall

LL14802D3

Lombardo.





Technical information:

Installation:	Wall, Surface mounting wall
Material:	Polycarbonate
Finish:	Dark Grey RAL 7021
Diffuser type:	Polycarbonate
Lamp type:	LED
Energy performance class:	F
Colour temperature:	3000K
CRI:	>80
LB Factor:	L80B50 - 50.000h
Photobiological risk:	RG1
Power consumption (Watt):	5
Lumen:	600
Real Lumen:	362
Power supply:	integrated
LED:	AC DIRECT
Insulation class:	CL.I
Type of protection:	**IP 65**
Resistance to breakage:	**IK 06 1J xx3**
Standards and Marks of Conformity:	CE UKCA
Dimming	Phase cut

GU10 version: light bulb not included.


Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it

Clic Wall

LL14802D3

Lombardo.





Installation images:










Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it

Clic Wall


LL14802D3

Lighting simulation:



clic_wall

Photometric curves:



Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it