Kit 05 - Tag 210 Garden

Lombardo.





Technical information:

Installation:	Ground
Material:	Aluminium
Finish:	Corten
Diffuser type:	Serigraphed glass
Lamp type:	LED
Colour temperature:	3000K
CRI:	>80
LB Factor:	L80B20 - 50.000h
Photobiological risk:	RG1
Power consumption (Watt):	25
Lumen:	3500
Real Lumen:	2585
Power supply:	⊘ integrated
LED:	220-240 V
Circuit breaker B10 - C10 - B16 - C16	22-27-32-41
Insulation class:	⊕ CL.I
Power cable:	1 m H05RN-F
Type of protection:	IP 66
Resistance to breakage:	IK 06 1J xx3
Standards and Marks of Conformity:	C € ĽK

Kit consisting of TAG 210 + LB1150035. **BORDO MARE**: add S to the end of the selected code including LED colour to have the product supplied with sea treatment against salt spray. Powder coating (on metal) ensures a matt and textured finish, while liquid coating (on plastic) provides brighter and more uniform aesthetic effects. The combined use of aluminium and plastic components can lead to variations in colour rendering, affecting the visual homogeneity of the final product.



Lombardo S.r.l. Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - T 0039 035 939 411 - E info@lombardo.it