


# Kit 06 - Tag 210 Asimmetrico Garden

**Lombardo.**

LL1151233



## Technical information:

Installation:	Ground
Material:	Aluminium
Finish:	White RAL 9010
Diffuser type:	Serigraphed glass
Lamp type:	LED
Colour temperature:	3000K
CRI:	>80
LB Factor:	L80B20 - 50.000h
Photobiological risk:	RG1
Power consumption (Watt):	25
Lumen:	3500
Real Lumen:	2386
Power supply:	✓ integrated
LED:	220-240 V
Circuit breaker	22-27-32-41
B10 - C10 - B16 - C16	
Insulation class:	Ⓜ CL.I
Power cable:	1 m H05RN-F
Type of protection:	<b>IP 66</b>
Resistance to breakage:	<b>IK 06 1J xx3</b>
Standards and Marks of Conformity:	CE UK CA

Kit consisting of TAG 210 Asimmetrico + LB1150035. **BORDO MARE:** add S to the end of the selected code including LED colour to have the product supplied with sea treatment against salt spray. Powder coating (on metal) ensures a matt and textured finish, while liquid coating (on plastic) provides brighter and more uniform aesthetic effects. The combined use of aluminium and plastic components can lead to variations in colour rendering, affecting the visual homogeneity of the final product.

