

Kit 06 - Tag 210 Asimmetrico Garden

LL115126 □

LOMBARDO



Available colours:

White RAL 9010

Grey High Tech RAL 9006

Grey anthracite RAL 7021

Corten



Technical information:

Type of product:	Ground recess
Diffuser type:	Serigraphed glass
Lamp type:	LED
Energy performance class:	A++
Colour temperature:	N 4000K 3 3000K, lm -5% 2 2700K, lm -5%
CRI:	>80
LB Factor 50.000 h:	L80B20
Photobiological risk:	RG1
Watt:	25
Lumen:	3500
Real Lumen:	2386
Power supply:	220-240 V
Insulation class:	CL.I
Type of protection:	IP 66
Resistance to breakage:	IK 06 1J xx3
Standards and Marks of Conformity:	
Pieces per package:	1

Kit consisting of TAG 210 Asimmetrico + LB1150035.

Product description:

Kit-04: consisting of Tag 110 + Garden accessory. Inaccessible device, provided with 1m of prewired power cable H05RN-F. No risk of photobiological damage, RG0 group (EN62471).
Kit-05: consisting of Tag210 + Garden accessory. Prearranged for double power input. Provided with 1m of prewired power cable H05RN-F. No photobiological risk under normal operating conditions, RG1 low risk group (EN62471). **Kit-06:** consisting of assymetric Tag 210 + Garden accessory. Prearranged for double power input. Provided with 1m of prewired power cable H05RN-F. No photobiological risk under normal operating conditions, RG1 low risk group (EN62471). Also suitable for outdoor use. Die-cast aluminum Body and joint highly resistant to oxidation thanks to the zirconium based passivation treatment and the UV stabilized polyester resin coating. Heat tempered and serigraphed glass diffuser. Aluminum reflector. Silicone gaskets to maintain IP66 rating. A4 stainless steel nuts and bolts. 180° angle adjustment. Thermoplastic garden accessory for Tag 110/210. Suitable for outdoor use and ground application. **LED 4000K (N), 3000K (3) or 2700K (2). Integral ballast 220-240V.**