



Technical information:

Installation:	Wall, Surface mounting wall
Material:	Aluminium
Finish:	Grey anthracite RAL 7021
Diffuser type:	Frosted glass
Lamp type:	LED
Energy performance class:	E
Colour temperature:	3000K
CRI:	>80
LB Factor:	L80B20 - 50.000h
Photobiological risk:	RG1
Power consumption (Watt):	6
Lumen:	750
Real Lumen:	375
Power supply:	✓ integrated
LED:	220-240 V
Circuit breaker	31-52-50-85
B10 - C10 - B16 - C16	
Insulation class:	⊕ CL.I
Type of protection:	IP 66
Resistance to breakage:	IK 10 20J xx9
Standards and Marks of Conformity:	CE UK CA

BORDO MARE: add S to the end of the selected code including LED colour to have the product supplied with sea treatment against salt spray.

All parts in direct contact with the soil must never be covered by the soil itself or come into contact with aggressive chemicals (e.g. fertilisers, herbicides, pool and/or floor cleaning products, etc.). Clean parts covered with soil build-up or cement dust periodically. Outdoor products must be installed with the appropriate plastic accessories. They must not be installed directly on the ground or directly on concrete because contact between the two materials can create accelerated oxidation of the device.



Koi 120

LL1210063

Lombardo.




Koi 120

LL1210063

Lombardo.

Lighting simulation:



koi_120