

# Pik 80 H 500

LL1350063


**Lombardo.**



## Technical information:

Installation:	Ground
Material:	Aluminium
Finish:	Green Anodized Aluminium
Treatment:	Anodization
Diffuser type:	Polycarbonate
Lamp type:	LED
Energy performance class:	F
Colour temperature:	3000K
CRI:	>80
LB Factor:	L80B20 - 50.000h
Photobiological risk:	RG0
Power consumption (Watt):	4,5
Lumen:	520
Real Lumen:	245
Power supply:	✓ integrated
LED:	AC DIRECT
Insulation class:	⊕ CL.I
Power cable:	2 m H05RN-F 3x1
Type of protection:	<b>IP 65</b>
Resistance to breakage:	<b>IK 08 5J xx7</b>
Standards and Marks of Conformity:	CE UK EA



*All parts in direct contact with the soil must never be covered by the soil itself or come into contact with aggressive chemicals (e.g. fertilisers, herbicides, pool and/or floor cleaning products, etc.). Clean parts covered with soil build-up or cement dust periodically. Outdoor products must be installed with the appropriate plastic accessories. They must not be installed directly on the ground or directly on concrete because contact between the two materials can create accelerated oxidation of the device.*




# Pik 80 H 500

LL1350063

Lombardo.



## Installation images:




# Pik 80 H 500

LL1350063

Lombardo.

## Lighting simulation:



pik\_80\_h500