


Rol 600

IP 66 IK 10 20J xx9 C ^{UK} C ^{CA}	LED		COL.	CODE *
	W	LM REAL LM		
	35	4.200 3130	⊕ Ⓢ 220-240 V	LL156060□□
	35	4.200 3130	⊕ Ⓢ 220-240 V DALI2	LM156060□□




★ Complete the CODE ○ OPTIC S | 30° M | 50° E | 12 X 35° W | Wall-washer □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Predisposto per doppio ingresso alimentazione. | Double cable entry at the back. | Préparé pour une double alimentation. | Preparado para doble entrada de alimentación.

Rol 600 RGBW



IP 66 IK 10 20J xx9 C ^{UK} C ^{CA}	LED		COL.	CODE *
	W	LM REAL LM		
	35	4.200 2610	⊕ Ⓢ 220-240 V DMX 512	LX156060○




★ Complete the CODE ○ OPTIC S | 30° M | 50° E | 12 X 35° W | Wall-washer

Predisposto per doppio ingresso alimentazione. | Double cable entry at the back. | Préparé pour une double alimentation. | Preparado para doble entrada de alimentación.

Rol 900

IP 66 IK 10 20J xx9 C ^{UK} C ^{CA}	LED		COL.	CODE *
	W	LM REAL LM		
	50	6.100 4620	⊕ Ⓢ 220-240 V	LL156090□□
	50	6.100 4620	⊕ Ⓢ 220-240 V DALI2	LM156090□□




★ Complete the CODE ○ OPTIC S | 30° M | 50° E | 12 X 35° W | Wall-washer □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Predisposto per doppio ingresso alimentazione. | Double cable entry at the back. | Préparé pour une double alimentation. | Preparado para doble entrada de alimentación.

Rol 1200

IP 66 IK 10 20J xx9 C ^{UK} C ^{CA}	LED		COL.	CODE *
	W	LM REAL LM		
	70	8.200 6160	⊕ Ⓢ 220-240 V	LL156012□□
	70	8.200 6160	⊕ Ⓢ 220-240 V DALI2	LM156012□□



★ Complete the CODE ○ OPTIC S | 30° M | 50° E | 12 X 35° W | Wall-washer □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Predisposto per doppio ingresso alimentazione. | Double cable entry at the back. | Préparé pour une double alimentation. | Preparado para doble entrada de alimentación.