
Ross 280 Emergenza

LL1240683

Lombardo.







Technical information:

Installation:	Wall, Surface mounting wall
Finish:	White from moulding
Diffuser type:	Polycarbonate
Lamp type:	LED
Colour temperature:	3000K
CRI:	>80
LB Factor:	L80B20 - 50.000h
Photobiological risk:	RG1
Power consumption (Watt):	9
Lumen:	1080
Power supply:	integrated
LED:	220-240 V
Circuit breaker B10 - C10 - B16 - C16	64-80-90-100
Version with:	Maintained emergency 3h
Insulation class:	CL.II
Type of protection:	**IP 66**
Resistance to breakage:	**IK 10 20J xx9**
Standards and Marks of Conformity:	CE UK CA

Version supplied with sticker kit with emergency signs.





Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it

Ross 280 Emergenza

LL1240683






Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it

Ross 280 Emergenza


LL1240683

Lighting simulation:



ross_280_emergenza

Photometric curves:



Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it