












Stile Next 506L Asimmetrico

IP66 IK 06 1J xx3 CE UK EN	LED			COL.	CODE *	
	W	LM	REAL LM			
	3	310	38	  220-240 V	 LL663C□	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. | Double cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy. | Possibilità alimentazione double entrée. Réflecteur en aluminium primaire injecté EN-AB44100. | Preparado para doble entrada de alimentación. Reflector de fundición de aluminio primario EN-AB44100.





Stile Next 506L Asimmetrico Orizzontale

IP66 IK 06 1J xx3 CE UK EN	LED			COL.	CODE *	
	W	LM	REAL LM			
	4	490	70	  220-240 V	 LL665F□  S LL665F2□  S LL665FG□  S LL665FK□	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. | Double cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy. | Possibilità alimentazione double entrée. Réflecteur en aluminium primaire injecté EN-AB44100. | Preparado para doble entrada de alimentación. Reflector de fundición de aluminio primario EN-AB44100.

Stile Next 506E

IP66 IK 06 1J xx3 CE UK EN	LED			COL.	CODE *	
	W	LM	REAL LM			
	6	720	283	  220-240 V	 LL651D□	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per doppio ingresso alimentazione. | Double cable entry at the back. | Possibilità alimentazione double entrée. | Preparado para doble entrada de alimentación.