



Stile next zero 120T

LL677H □

LOMBARDO



Technical information:

Type of product:	Ground recess
Diffuser type:	Serigraphed glass
Lamp type:	LED
Energy performance class:	A++
Colour temperature:	N 4000K 3 3000K, lm -5%
CRI:	>80
Photobiological risk:	RG0
Watt:	4,5
Lumen:	725
Real Lumen:	260
Power supply:	✔ 220-240 V
Insulation class:	□ CL.II
Type of protection:	IP 67
Resistance to breakage:	IK 10 20J xx9
Standards and Marks of Conformity:	CE UK CB
Pieces per package:	4

Max temperature on the glass 55°C.

Product description:

Suitable for recessed flush ground application, also for outdoor use and drive-over, max load 2000 kgs. Body made of EN-AB44100 die-cast aluminium primary alloy; highly resistant to oxidization thanks to the zirconium-based passivation treatment and UV stabilized polyester resin coating. Heat tempered and serigraphed glass diffuser, 10 mm thickness, integral to the aluminium body with a double layer of high resistant resin. 3 metre pre-wired cable type H05RN-F, secured by means of a back resin preventing any access to the fixture. The fixture is fixed to the appropriate recessed box - supplied separately - by means of retaining springs. Nuts and bolts in A4 stainless steel or AISI 316L. Patented model. **LED 4000K (N) or 3000K (3) LED. Integral ballast 220-240V. No risk of photobiological damage, RG0 group (EN62471)**

Stile next zero 120T

LL677H □

LOMBARDO

