

















CNC 99 CL

IP67 IK 10 20J xx9 Ⓛ 2000 ^{KG} MAX 53°C MAX CE UK CR	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	45	 LL137000 <input type="checkbox"/>  LL13700W <input type="checkbox"/>  LL13700G <input type="checkbox"/>  LL13700E <input type="checkbox"/>  LL13700K <input type="checkbox"/>	 24V	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Cod. LL137000N/3/2 ghiera in acciaio inox. Se installato con armatura cod. LB1230001, il prodotto è calpestabile. | Cod. LL137000N/3/2 stainless steel retaining ring. When installed with recess box code LB1230001, the product is walk-over. | Cod. LL137000N/3/2 collerette en acier inox. Lorsqu'il est installé avec le code d'armature LB1230001, le produit est praticable.









CNC 99 C2L

IP67 IK 10 20J xx9 Ⓛ 2000 ^{KG} MAX 53°C MAX CE UK CR	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	100	 LL137010 <input type="checkbox"/>  LL13701W <input type="checkbox"/>  LL13701G <input type="checkbox"/>  LL13701E <input type="checkbox"/>  LL13701K <input type="checkbox"/>	 24V	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Cod. LL137010N/3/2 ghiera in acciaio inox. Se installato con armatura cod. LB1230001, il prodotto è calpestabile. | Bidirectional version. Cod. LL137010N/3/2 stainless steel retaining ring. When installed with recess box code LB1230001, the product is walk-over. | Cod. LL137010N/3/2 collerette en acier inox. Lorsqu'il est installé avec le code d'armature LB1230001, le produit est praticable.









CNC 99 C4L

IP67 IK 10 20J xx9 Ⓛ 2000 ^{KG} MAX 53°C MAX CE UK CR	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	200	 LL137020 <input type="checkbox"/>  LL13702W <input type="checkbox"/>  LL13702G <input type="checkbox"/>  LL13702E <input type="checkbox"/>  LL13702K <input type="checkbox"/>	 24V	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Cod. LL137020N/3/2 ghiera in acciaio inox. Se installato con armatura cod. LB1230001, il prodotto è calpestabile. | Cod. LL137020N/3/2 stainless steel retaining ring. When installed with recess box code LB1230001, the product is walk-over. | Cod. LL137020N/3/2 collerette en acier inox. Lorsqu'il est installé avec le code d'armature LB1230001, le produit est praticable.

CNC 99 C180

IP67 IK 10 20J xx9 Ⓛ 2000 ^{KG} MAX 53°C MAX CE UK CR	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	93	 LL137030 <input type="checkbox"/>  LL13703W <input type="checkbox"/>  LL13703G <input type="checkbox"/>  LL13703E <input type="checkbox"/>  LL13703K <input type="checkbox"/>	 24V	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione a 180°. Cod. LL137030N/3/2 ghiera in acciaio inox. Se installato con armatura cod. LB1230001, il prodotto è calpestabile. | 180° version. Cod. LL137030N/3/2 stainless steel retaining ring. When installed with recess box code LB1230001, the product is walk-over. | Version 180°. Cod. LL137030N/3/2 collerette en acier inox. Lorsqu'il est installé avec le code d'armature LB1230001, le produit est praticable.