































INC

INC 35			DIFF. VETRO	POSITION 			
IP 67 IK 10 20J xx9   500  500  65° MAX							
LED	W	LM	REAL LM	COL.	CODE * *	* OPTIC	* LED COLOUR
A++	2	180	120		LL132000  LL132001  LL132002 	S 14° M 29° L 46°	N 4000K 3 3000K, lm -5% 2 2700K, lm -5%
A++	2	180	120		LL132003  LL132004  LL132005 		

Versione ghiera tonda, possibile scelta di 3 differenti ottiche. Temperatura massima rilevata sul vetro 65°C.

Version with round retaining ring, choice of 3 different optics. Max. temperature measured on the glass 65°C.

Version avec virole ronde, choix possible de 3 optiques différentes. Température relevée sur le verre 65°C maxi.

INC 50			DIFF. VETRO	POSITION 			
IP 67 IK 10 20J xx9   500  500  65° MAX							
LED	W	LM	REAL LM	COL.	CODE * *	* OPTIC	* LED COLOUR
A++	6,5	650	418		LL132006  LL132007  LL132008 	S 13° M 24° L 53°	N 4000K 3 3000K, lm -5% 2 2700K, lm -5%
A++	6,5	650	418		LL132009  LL132010  LL132011 		


Versione ghiera tonda, possibile scelta di 3 differenti ottiche. Temperatura massima rilevata sul vetro 65°C.


Version with round retaining ring, choice of 3 different optics. Max. temperature measured on the glass 65°C.

Version avec virole ronde, choix possible de 3 optiques différentes. Température relevée sur le verre 65°C maxi.



Finishing

 Inox satinato
Satin grey
Inox satiné

 Bianco RAL 9010
White RAL 9010
Blanc RAL 9010

 Grigio antracite RAL 7021
Grey anthracite RAL 7021
Gris anthracite RAL 7021

* Led colour

N 4000K
3 3000K, lm -5%
2 2700K, lm -5%

Completa il codice sostituendo al quadrato rosso la lettera o il numero corrispondente alla temperatura colore scelta.

Complete the code by replacing the red box with the letter or number corresponding to the selected colour temperature.

Compléter le code en remplaçant le carré rouge par la lettre ou le numéro correspondant à la sélection de température couleur.

Alimentatore escluso

Ballast not included
Sans alimentation

