





Stile next 103

| IP66 IK 06 1J xx3 CE UK ER | LED | | | | |
|----------------------------------|-----|-----|---------|---|---|
| | W | LM | REAL LM | COL. | CODE * |
| | 3 | 310 | 68 | ⊕ ⊖ 220-240 V |  LL642C□ |
| | 6 | 720 | 170 | ⊕ ⊖ 220-240 V |  LL642D□ |
| 3 | 360 | 85 | ⊕ ⊖ 24V |  LL643D□ | |





95x70 mm
3 3/4" x 2 3/4"

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per singolo ingresso alimentazione. LL643DN/3 alimentatore escluso. | Single cable entry at the back. LL643DN/3 ballast not included. | Entrée d'alimentation simple. LL643DN/3 ballast exclus.

Stile next 103 asimmetrica

| IP66 IK 06 1J xx3 CE UK ER | LED | | | | |
|----------------------------------|-----|----|---------------|---|--------|
| | W | LM | REAL LM | COL. | CODE * |
| 3 | 310 | 45 | ⊕ ⊖ 220-240 V |  LL644C□ | |







95x70 mm
3 3/4" x 2 3/4"

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per singolo ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB4+100. | Single cable entry at the back. Reflector made of EN-AB4+100 die-cast aluminium primary alloy. | Entrée d'alimentation simple. Réflecteur en aluminium primaire injecté EN-AB4+100

Stile next 106L

| IP66 IK 06 1J xx3 CE UK ER | LED | | | | |
|----------------------------------|-----|-----|---------------|---|---|
| | W | LM | REAL LM | COL. | CODE * |
| | 6 | 720 | 217 | ⊕ ⊖ 220-240 V |  LL662D□ |
| | 6 | 720 | 217 | ⊕ ⊖ 24V |  LL663D□ |
| 3 | 270 | 94 | ⊕ ⊖ 220-240 V |  LL6623□ | |



172x68 mm
6 3/4" x 2 5/8"

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per doppio ingresso alimentazione. LL663DN/3 alimentatore escluso. | Double cable entry at the back. LL663DN/3 ballast not included. | Possibilité alimentation double entrée. LL663DN/3 ballast exclus.