













































# Ago Bollard

<b>Ago Bollard H300 1L</b> 		<b>DIFF. TRASP.</b>	<b>POSITION</b> 			
<b>IP66 IK 07 2J xx5 CE</b>						
<b>LED</b>	<b>W</b>	<b>LM</b>	<b>REAL LM</b>	<b>COL.</b>	<b>CODE *</b>	<b>* LED COLOUR</b>
A++	10	1100	270	  <b>220-240 V</b>	 <b>LL126318</b> 	 4000K  3000K, lm -5%  2700K, lm -5%
					 <b>LL126319</b> 	
					 <b>LL126320</b> 	
A++	10	1100	270	 	 <b>LT126318</b> 	
					 <b>LT126319</b> 	
					 <b>LT126320</b> 	

Versione monoemissione.

Unidirectional version.























Version unidirectionnelle.

<b>Ago Bollard H300 2L</b> 		<b>DIFF. TRASP.</b>	<b>POSITION</b> 			
<b>IP66 IK 07 2J xx5 CE</b>						
<b>LED</b>	<b>W</b>	<b>LM</b>	<b>REAL LM</b>	<b>COL.</b>	<b>CODE *</b>	<b>* LED COLOUR</b>
A++	10	1100	540	  <b>220-240 V</b>	 <b>LL126321</b> 	 4000K  3000K, lm -5%  2700K, lm -5%
					 <b>LL126322</b> 	
					 <b>LL126323</b> 	
A++	10	1100	540	 	 <b>LT126321</b> 	
					 <b>LT126322</b> 	
					 <b>LT126323</b> 	

Versione biemissione.

Bidirectional version.

Version bidirectionnelle.



<b>Ago Bollard H600 1L</b> 		<b>DIFF. TRASP.</b>	<b>POSITION</b> 			
<b>IP66 IK 07 2J xx5 CE</b>						
<b>LED</b>	<b>W</b>	<b>LM</b>	<b>REAL LM</b>	<b>COL.</b>	<b>CODE *</b>	<b>* LED COLOUR</b>
A++	10	1100	270	  <b>220-240 V</b>	 <b>LL126300</b> 	 4000K  3000K, lm -5%  2700K, lm -5%
					 <b>LL126301</b> 	
					 <b>LL126302</b> 	
A++	10	1100	270	 	 <b>LT126300</b> 	
					 <b>LT126301</b> 	
					 <b>LT126302</b> 	


Versione monoemissione.

Unidirectional version.



Version unidirectionnelle.

## Finishing

 Alluminio Anodizzato Grigio  
 Grey Anodized Aluminum  
 Aluminium anodisé Gris  
 Alluminio Anodizzato Nero  
 Black Anodized Aluminum  
 Aluminium anodisé Noir

 Alluminio Anodizzato Marrone  
 Brown Anodized Aluminum  
 Aluminium anodisé Marron

## \* Led colour

 4000K  
 3000K, lm -5%  
 2700K, lm -5%

**Completa il codice** sostituendo al quadrato rosso la lettera o il numero corrispondente alla temperatura colore scelta.

**Complete the code** by replacing the red box with the letter or number corresponding to the selected colour temperature.

**Compléter le code** en remplaçant le carré rouge par la lettre ou le numéro correspondant à la sélection de température couleur.

## Alimentazione diretta

Integral ballast  
 Alimentation intégrée

 **220-240 V**

## Alimentatore escluso

Ballast not included  
 Sans alimentation

