









CNC 25 T




IP67 IK 10 20J xx9 CE UK CR 500 KG MAX 65°C MAX	LED			COL.	CODE *
	W	LM	REAL LM		
 Fino ad esaurimento. Until our stock lasts. Jusqu'à épuisement de stock. Hasta el agotamiento del stock.	2	180	Max 148	  	LL119000□□ LL119004□□ LL119006□□
	2	180	Max 148	  	LL119001□□ LL119005□□ LL119007□□




* Complete the CODE ○ OPTIC S | 15° M | 30° D | Diff. □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K B | Blue

Idoneo per installazione in tubo corrugato standard Ø25 mm. | Suitable for installation in standard Ø 25 mm corrugated duct. | Convient pour une installation dans un tube annelé standard Ø25 mm. | Adecuado para instalación en tubo corrugado estándar Ø 25 mm.

CNC 25 Q

IP67 IK 10 20J xx9 CE UK CR 500 KG MAX 65°C MAX	LED			COL.	CODE *
	W	LM	REAL LM		
 Fino ad esaurimento. Until our stock lasts. Jusqu'à épuisement de stock. Hasta el agotamiento del stock.	2	180	Max 148		LL119002□□
	2	180	Max 148		LL119003□□



* Complete the CODE ○ OPTIC S | 15° M | 30° D | Diff. □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K B | Blue

Idoneo per installazione in tubo corrugato standard Ø25 mm. | Suitable for installation in standard Ø 25 mm corrugated duct. | Convient pour une installation dans un tube annelé standard Ø25 mm. | Adecuado para instalación en tubo corrugado estándar Ø 25 mm.