
















CNC 99 C Up

| IP67 IK 10 20J xx9 ↓ 500 KG MAX ↑ 53°C MAX CE UK CA | LED | | | COL. | CODE * |  |
|---|-----|-----|---------|---|---|---|
| | W | LM | REAL LM | | | |
|  | 5 | 470 | 173 |  × 24V | <ul style="list-style-type: none">  LL137040□  LL13704W□  LL13704G□  LL13704E□  LL13704K□ | |

* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Cod. LL137040N/3/2 ghiera in acciaio inox. Diffusore in policarbonato, effetto poliGLASS. | Cod. LL137040N/3/2 stainless steel retaining ring. Polycarbonate diffuser, polyGLASS effect. | Cod. LL137040N/3/2 collerette en acier inox. Diffuseur en polycarbonate, effet polyGLASS. | Cod. LL137040N/3/2 casquillos de acero inoxidable. Difusor de policarbonato, efecto polyGLASS.








CNC 99 QL

| IP67 IK 10 20J xx9 ↓ 2000 KG MAX ↑ 53°C MAX CE UK CA | LED | | | COL. | CODE * |  |
|---|-----|-----|---------|---|--|---|
| | W | LM | REAL LM | | | |
|  | 5 | 470 | 52 |  × 24V | <ul style="list-style-type: none">  LL13710W□  LL13710G□  LL13710E□  LL13710K□ | |

* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. | When installed with recess box code LB1230001, all models are walk-over. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables.








CNC 99 Q2L

| IP67 IK 10 20J xx9 ↓ 2000 KG MAX ↑ 53°C MAX CE UK CA | LED | | | COL. | CODE * |  |
|---|-----|-----|---------|---|--|---|
| | W | LM | REAL LM | | | |
|  | 5 | 470 | 98 |  × 24V | <ul style="list-style-type: none">  LL13711W□  LL13711G□  LL13711E□  LL13711K□ | |

* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. | When installed with recess box code LB1230001, all models are walk-over. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables.

CNC 99 Q4L

| IP67 IK 10 20J xx9 ↓ 2000 KG MAX ↑ 53°C MAX CE UK CA | LED | | | COL. | CODE * |  |
|---|-----|-----|---------|---|--|---|
| | W | LM | REAL LM | | | |
|  | 5 | 470 | 170 |  × 24V | <ul style="list-style-type: none">  LL13712W□  LL13712G□  LL13712E□  LL13712K□ | |

* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. | When installed with recess box code LB1230001, all models are walk-over. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables.