


Delta 2 Simmetrico

IP66 IK 08 5J xx7 CE UK CA	LED			COL.	CODE *
	W	LM MAX.	REAL LM MAX.		
	75	12.500	11.463	⊕ ✓ 220-240 V	LL15421WS1□
					LL15421GS1□
					LL15421KS1□
					LL15421BS1□
	75	12.500	11.463	⊕ ✓ 220-240 V DALI2	LM15421WS1□
					LM15421GS1□
					LM15421KS1□
					LM15421BS1□
	100	15.000	13.643	⊕ ✓ 220-240 V	LL15422WS1□
					LL15422GS1□
					LL15422KS1□
					LL15422BS1□
	100	15.000	13.643	⊕ ✓ 220-240 V DALI2	LM15422WS1□
					LM15422GS1□
					LM15422KS1□
					LM15422BS1□
	120	17.500	16.052	⊕ ✓ 220-240 V	LL15423WS1□
					LL15423GS1□
					LL15423KS1□
					LL15423BS1□
	120	17.500	16.052	⊕ ✓ 220-240 V DALI2	LM15423WS1□
					LM15423GS1□
					LM15423KS1□
					LM15423BS1□



* Complete the CODE □ LED COLOUR 5 | 5700K N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione on-off: cavo 0,7m H05RN-F. Versione DALI: cavo 0,7m H07RN-F. | On-off version cable: 0,7m H05RN-F. Cable DALI version: 0,7m H07RN-F. | Câble version on-off : 0,7m H05RN-F. Câble version DALI : 0,7m H07RN-F. | Cable versión on-off: 0,7m H05RN-F. Cable versión DALI: 0,7m H07RN-F.