















































Dodo 60

IP54 IK 10 20J xx9 	LED			COL. CODE *													
	W	LM	REAL LM														
	3	360	120	  AC DIRECT	<table border="0"> <tr><td></td><td>LL14301W</td></tr> <tr><td></td><td>LL14301L</td></tr> <tr><td></td><td>LL14301D</td></tr> <tr><td></td><td>LL14301Z</td></tr> <tr><td></td><td>LL14301B</td></tr> <tr><td></td><td>LL14301S</td></tr> </table>		LL14301W		LL14301L		LL14301D		LL14301Z		LL14301B		LL14301S
	LL14301W																
	LL14301L																
	LL14301D																
	LL14301Z																
	LL14301B																
	LL14301S																

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Fasci disponibili: 15°, 30°, 60°, regolabili tramite mascherine sostituibili. | Available light beams: 15°, 30°, 60°, adjustable with removable masks. | Faisceaux disponibles : 15°, 30°, 60°, réglables avec masques amovibles. | Haces disponibles: 15°, 30°, 60°, ajustables mediante máscaras intercambiables.

Dodo 60 Full

IP54 IK 10 20J xx9 	LED			COL. CODE *													
	W	LM	REAL LM														
	3	360	83	  AC DIRECT	<table border="0"> <tr><td></td><td>LL14302W</td></tr> <tr><td></td><td>LL14302L</td></tr> <tr><td></td><td>LL14302D</td></tr> <tr><td></td><td>LL14302Z</td></tr> <tr><td></td><td>LL14302B</td></tr> <tr><td></td><td>LL14302S</td></tr> </table>		LL14302W		LL14302L		LL14302D		LL14302Z		LL14302B		LL14302S
	LL14302W																
	LL14302L																
	LL14302D																
	LL14302Z																
	LL14302B																
	LL14302S																

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Fasci disponibili: 15°, 30°, 60°, regolabili tramite mascherine sostituibili. | Available light beams: 15°, 30°, 60°, adjustable with removable masks. | Faisceaux disponibles : 15°, 30°, 60°, réglables avec masques amovibles. | Haces disponibles: 15°, 30°, 60°, ajustables mediante máscaras intercambiables.

Accessori | Accessories | Accessoires | Accesorios

Bus DALI

Variatore universale comandabile con segnale PUSH/DALI. Dimmerazione a Taglio di Fase discendente (a fine fase) IGBT Trailing-Edge.

Col.	Code
	LB1070110

Bus DALI

Universal dimmer controlled by PUSH/DALI signal. Descending Phase Cutting dimming (at the end of the phase) IGBT Trailing-Edge.

Bus DALI

Variateur universel commandé par un signal PUSH/DALI. Phase descendante Gradation par coupure (à la fin de la phase) IGBT Trailing-Edge.

Bus DALI

Dimmer universal controlado por señal PUSH/DALI. Atenuación por corte de fase descendente (al final de la fase) IGBT Trailing-Edge.

