


Pad Mini



IP66 IK 08 5J xx7 CE UK CA	LED			COL.	CODE *
	W	LM	REAL LM		
	8	1000	795	⊕ ⊙ 220-240 V	LL157010□□ LL157015□□
	8	1000	795	⊕ ⊙ 24V	LT157010□□ LT157015□□




★ Complete the CODE ○ OPTIC S | 12° M | 20° A | 20° X 45° □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione on-off: cavo 0,8m H07RN-F 3X1. Versione 24V: cavo 0,8m Li9Y11Y 2X0,75mmq / PUR H.F 300V. | On-off version cable: 0,8m H07RN-F 3X1. Cable 24V version: 0,8m Li9Y11Y 2X0,75mmq / PUR H.F 300V. | Câble version on-off : 0,8m H07RN-F 3X1. Câble version 24V: 0,8m Li9Y11Y 2X0,75mmq / PUR H.F 300V. | Cable versión on-off: 0,8m H07RN-F 3X1. Cable versión 24V: 0,8m Li9Y11Y 2X0,75mmq / PUR H.F 300V.

Pad

IP66 IK 08 5J xx7 CE UK CA	LED			COL.	CODE *
	W	LM	REAL LM		
	20	2.550	2030	⊕ ⊙ 220-240 V	LL157000□□ LL157005□□
	20	2.550	2030	⊕ ⊙ 220-240 V DALI2	LM157000□□ LM157005□□




★ Complete the CODE ○ OPTIC S | 10° M | 30° A | 15° X 40° □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione on-off: cavo 0,8m H07RN-F 3X1. Versione DALI: cavo 0,8m H07RN-F 5×1,5. | Cable on-off version: 0,8m H07RN-F 3X1. Cable DALI version: 0,8m H07RN-F 5×1,5. | Câble version on-off : 0,8m H07RN-F 3X1. Câble version DALI: 0,8m H07RN-F 5×1,5. | Cable versión on-off: 0,8m H07RN-F 3X1. Cable versión DALI: 0,8m H07RN-F 5×1,5.

Pad RGBW



IP66 IK 08 5J xx7 CE UK CA	LED			COL.	CODE *
	W	LM	REAL LM		
	27	2.250	1070	⊕ ⊙ 24V	LX157000□□ LX157005□□
			DMX 512		



★ Complete the CODE ○ OPTIC S | 10° M | 30° A | 15° X 40°

Cavo: 0,8m Li2YCYv (TP) 2X0,75. | Cable: 0,8m Li2YCYv (TP) 2X0,75. | Câble: 0,8m Li2YCYv (TP) 2X0,75. | Cable: 0,8m Li2YCYv (TP) 2X0,75.

