


Stile Next 503

IP66 IK 06 1J xx3 CE UK CA	LED				COL.	CODE *
	W	LM	REAL LM			
	3	310	68	⊕ ⊙ 220-240 V	   	LL641C□ LL641C2□ LL641CG□ LL641CK□
	6	720	170	⊕ ⊙ 220-240 V		LL641D□




★ Complete the CODE ☐ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K, only for 3W version

Predisposto per singolo ingresso alimentazione. Versione a 6W, cod. LL641D_, non disponibile in 2700K. | Single cable entry at the back. 6W version, code LL641D_, not available in 2700K. | Entrée d'alimentation simple. Version 6W, code LL641D_, non disponible en 2700K. | Preparado para la entrada de una única alimentación. Versión de 6W, código LL641D_, no disponible en 2700K.

Stile Next 503 Asimmetrico

IP66 IK 06 1J xx3 CE UK CA	LED				COL.	CODE *
	W	LM	REAL LM			
	3	310	45	⊕ ⊙ 220-240 V	   	LL643C□ LL643C2□ LL643CG□ LL643CK□




★ Complete the CODE ☐ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Predisposto per singolo ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. | Single cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy. | Entrée d'alimentation simple. Réflecteur en aluminium primaire injecté EN-AB44100. | Preparado para la entrada de una única alimentación. Reflector de fundición de aluminio primario EN-AB44100.

Stile Next 506L

IP66 IK 06 1J xx3 CE UK CA	LED				COL.	CODE *
	W	LM	REAL LM			
	6	720	217	⊕ ⊙ 220-240 V	   	LL661D□ LL661D2□ LL661DG□ LL661DK□



★ Complete the CODE ☐ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Predisposto per doppio ingresso alimentazione. | Double cable entry at the back. | Possibilit  alimentazione double entr e. | Preparado para doble entrada de alimentaci n.