

## Clic Garden



<b>IP65 IK 06 1J xx3</b> CE UK ER	LED		COL.		CODE *
	W	LM	REAL LM		
5	600	362	⊕ ⊖ AC DIRECT	LL14803B□ LL14803D□ LL14803K□ LL14803V□	
LAMP		ATT. MAX		CFL	
GU10 1x7		□	LU14803B LU14803K		

\* Complete the CODE     LED COLOUR    N | 4000K    3 | 3000K    2 | 2700K  
 Versione GU10: lampadina non inclusa.    |    GU10 version: light bulb not included.    |    Version GU10: ampoule non incluse.

## Clic Up Garden



<b>IP65 IK 06 1J xx3</b> CE UK ER	LED		COL.		CODE *
	W	LM	REAL LM		
5	600	330	⊕ ⊖ AC DIRECT	LL14813B□ LL14813D□ LL14813K□ LL14813V□	
LAMP		ATT. MAX		CFL	
GU10 1x7		□	LU14813B LU14813K		

\* Complete the CODE     LED COLOUR    N | 4000K    3 | 3000K    2 | 2700K  
 Versione GU10: lampadina non inclusa.    |    GU10 version: light bulb not included.    |    Version GU10: ampoule non incluse.

## Accessori | Accessories | Accessoires

### Bus DALI

**Variluce universale comandabile con segnale DALI. Dimmerazione a Taglio di Fase discendente (a fine fase) IGBT Trailing-Edge.**

Col.	Code
-	LB1070110

#### Bus DALI

Universal dimmer controlled by DALI signal. Descending Phase Cutting dimming (at the end of the phase) IGBT Trailing-Edge.

#### Bus DALI

Variateur universel commandé par un signal DALI. Phase descendante Gradation par coupure (à la fin de la phase) IGBT Trailing-Edge.

