



























CNC 100

CNC 100 L				DIFF. SEMITRASP.		
IP 68 IK 10 20J xx9    						
LED	W	LM	REAL LM	COL.	CODE *	* LED COLOUR
3	215	103	  220-240 V		LL123000  LL123001  LL123002  LL123003  LL123004 	N 4000K 3 3000K, lm -5% 2 2700K, lm -5%

Versione ghiera top con apertura a 110°. Temperatura massima rilevata sul diffusore 50°C.
Cavo H05RN-F 3x1.

Version with Top retaining ring with 110° opening. Max. temperature measured on the diffuser 50°C.
Cable type H05RN-F 3x1.














Version avec virole Top ouverture à 110°. Température relevée sur le diffuseur 50° C maxi.
Câble H05RN-F 3x1.

CNC 100 2L				DIFF. SEMITRASP.		
IP 68 IK 10 20J xx9    						
LED	W	LM	REAL LM	COL.	CODE *	* LED COLOUR
5	430	205	  220-240 V		LL123005  LL123006  LL123007  LL123008  LL123009 	N 4000K 3 3000K, lm -5% 2 2700K, lm -5%

Versione ghiera con 2 aperture da 110°. Temperatura massima rilevata sul diffusore 50°C.
Cavo H05RN-F 3x1.

Version with Top retaining ring with two 110° openings. Max. temperature measured on the diffuser 50°C.
Cable type H05RN-F 3x1.

Version avec virole Top 2 ouvertures à 110°. Température relevée sur le diffuseur 50° C maxi.
Câble H05RN-F 3x1.

CNC 100 UP				DIFF. POLIGLASS		
IP 68 IK 10 20J xx9    						
LED	W	LM	REAL LM	COL.	CODE *	* LED COLOUR
4	400	217	  220-240 V		LL123010  LL123011  LL123012  LL123013  LL123014 	N 4000K 3 3000K, lm -5% 2 2700K, lm -5%

Emissione luminosa a 120°. Temperatura massima rilevata sul diffusore 50°C. Versione calpestabile.
Cavo H05RN-F 3x1.

Light beam 120°. Max. temperature measured on the diffuser 50°C. Walk-over version.
Cable type H05RN-F 3x1.

Angle de diffusion 120°. Température relevée sur le diffuseur 50° C maxi. Version piétinabile.
Câble H05RN-F 3x1.