









**CNC 100 L**









IP67 I K 10 20J xx9 CE UK CA 2000 KG MAX 50°C MAX	LED			COL.	CODE *	
	W	LM	REAL LM			
	3	215	103	 LL123000□  LL123001□  LL123002□  LL123003□  LL123004□	  220-240 V	

Fino ad esaurimento.  
Until our stock lasts.  
Jusqu'à épuisement de stock.  
Hasta el agotamiento del stock.

\* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione ghiera top con apertura a 110°. Cavo H05RN-F 3×1. | Version with Top retaining ring with 110° opening. Cable type H05RN-F 3×1. | Version avec virole Top ouverture à 110°. Câble H05RN-F 3×1. | Versión casquillo Top con apertura a 110°. Cable H05RN-F 3×1.

**CNC 100 2L**









IP67 I K 10 20J xx9 CE UK CA 2000 KG MAX 50°C MAX	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	430	205	 LL123005□  LL123006□  LL123007□  LL123008□  LL123009□	  220-240 V	

Fino ad esaurimento.  
Until our stock lasts.  
Jusqu'à épuisement de stock.  
Hasta el agotamiento del stock.

\* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione ghiera con 2 aperture da 110°. Cavo H05RN-F 3×1. | Version with Top retaining ring with two 110° openings. Cable type H05RN-F 3×1. | Version avec virole Top 2 ouvertures à 110°. Câble H05RN-F 3×1. | Versión casquillo Top con 2 aperturas de 110°. Cable H05RN-F 3×1.

**CNC 100 Up**

IP67 IK 10 20J xx9 CE UK CA 280 KG MAX 50°C MAX	LED			COL.	CODE *	
	W	LM	REAL LM			
	4	400	217	 LL123010□  LL123011□  LL123012□  LL123013□  LL123014□	  220-240 V	

Fino ad esaurimento.  
Until our stock lasts.  
Jusqu'à épuisement de stock.  
Hasta el agotamiento del stock.

\* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Emissione luminosa a 120°. Cavo H05RN-F 3×1. | Light beam 120°. Cable type H05RN-F 3×1. | Angle de diffusion 120°. Câble H05RN-F 3×1. | Emissione luminosa a 120°. Cable H05RN-F 3×1.