

CNC 35 Q Up

IP 67 I

K 10 20J xx9


CE UK CA 1000 KG MAX

65°C MAX



Fino ad esaurimento.
Until our stock lasts.
Jusqu'à épuisement de stock.
Hasta el agotamiento del stock.

LED					
W	LM	REAL LM		COL.	CODE *
2	180	78	500mA-4,8V		LL107026□
2	180	78	12/24V		LL107027□



★ Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K B | Blue

Versione con diffusore in vetro sporgente ad alta diffondenza. | Version with protruding glass diffuser for high diffusion. | Version avec diffuseur en verre saillant à diffusion élevée. | Versión con difusor de vidrio sobresaliente de alta difusión.

CNC 35 Top S

IP 67

IK 10 20J xx9


CE UK CA 500 KG MAX

65°C MAX



Fino ad esaurimento.
Until our stock lasts.
Jusqu'à épuisement de stock.
Hasta el agotamiento del stock.

LED					
W	LM	REAL LM		COL.	CODE *
2	180	12	500mA-4,8V		LL107002□
2	180	12	12/24V		LL107008□



★ Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K B | Blue

Versione ghiera Top con apertura a 45°. | Version with Top retaining ring with 45° opening. | Version avec virole Top ouverture à 45°. | Versión casquillo Top con apertura a 45°.

CNC 35 Top L

IP 67

IK 10 20J xx9


CE UK CA 500 KG MAX

65°C MAX



Fino ad esaurimento.
Until our stock lasts.
Jusqu'à épuisement de stock.
Hasta el agotamiento del stock.

LED					
W	LM	REAL LM		COL.	CODE *
2	180	25	500mA-4,8V		LL107003□
2	180	25	12/24V		LL107009□



★ Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K B | Blue

Versione ghiera top con apertura a 135°. | Version with Top retaining ring with 135° opening. | Version avec virole Top ouverture à 135°. | Versión casquillo Top con apertura a 135°.