

# Kit Pin

<b>Kit 01 - Pin T</b>		<b>DIFF. TRASP.</b>	<b>POSITION</b> 									
<b>IP66 IK 07 2J xx5 CE</b>												
<b>LED</b>	<b>W</b>	<b>LM</b>	<b>REAL LM</b>	<b>COL.</b>	<b>CODE *</b>	<b>* LED COLOUR</b>						
A++	2	200	56		220-240 V	<table border="1"> <tr> <td>N</td> <td>4000K</td> </tr> <tr> <td>3</td> <td>3000K, lm -5%</td> </tr> <tr> <td>2</td> <td>2700K, lm -5%</td> </tr> </table>	N	4000K	3	3000K, lm -5%	2	2700K, lm -5%
N	4000K											
3	3000K, lm -5%											
2	2700K, lm -5%											
					S LL125100□							
					S LL125101□							
					S LL125102□							
					S LL125103□							

KIT composto da Pin T + LB1250001.

Kit consisting of Pin T + LB1250001.

Kit composé des Pin T + LB1250001.

<b>Kit 02 - Pin T Asimmetrico</b>		<b>DIFF. TRASP.</b>	<b>POSITION</b> 									
<b>IP66 IK 07 2J xx5 CE</b>												
<b>LED</b>	<b>W</b>	<b>LM</b>	<b>REAL LM</b>	<b>COL.</b>	<b>CODE *</b>	<b>* LED COLOUR</b>						
A++	2	200	67		220-240 V	<table border="1"> <tr> <td>N</td> <td>4000K</td> </tr> <tr> <td>3</td> <td>3000K, lm -5%</td> </tr> <tr> <td>2</td> <td>2700K, lm -5%</td> </tr> </table>	N	4000K	3	3000K, lm -5%	2	2700K, lm -5%
N	4000K											
3	3000K, lm -5%											
2	2700K, lm -5%											
					S LL125104□							
					S LL125105□							
					S LL125106□							
					S LL125107□							

KIT composto da Pin T Asimmetrico + LB1250001.

Kit consisting of Pin T Asimmetrico + LB1250001.

Kit composé des Pin T Asimmetrico + LB1250001.

## Finishing



Neutro  
Neutral  
Neutre



Serigrafia Nera  
Black serigraphy  
Sérigraphie noir



S Serigrafia Grigio High Tech  
Grey High Tech Serigraphy  
Sérigraphie Gris High Tech



S Serigrafia Corten  
Corten serigraphy  
Sérigraphie Corten

## \* Led colour

- N 4000K
- 3 3000K, lm -5%
- 2 2700K, lm -5%

**Completa il codice** sostituendo al quadrato rosso la lettera o il numero corrispondente alla temperatura colore scelta.

**Complete the code** by replacing the red box with the letter or number corresponding to the selected colour temperature.

**Compléter le code** en remplaçant le carré rouge par la lettre ou le numéro correspondant à la sélection de température couleur.

## Alimentazione diretta

Integral ballast  
Alimentation intégrée

220-240 V

## Alimentatore escluso

Ballast not included  
Sans alimentation

