



OLA



- ↳ Ola 330
- ↳ Ola 330 Color
- ↳ Ola 500
- ↳ Ola 500 Color

OLA

Installazione
Installation
Installation

Parete - Soffitto
Wall - Ceiling
Mur - Plafond

Materiali
Materials
Materiels

Tipo di diffusore: PMMA
Diffuser type: PMMA
Type de diffuseur: PMMA

Alimentazione
Power supply
Alimentation

AC DIRECT

Versioni
Versions
Versions

Taglio di fase
Phase cut
Coupure de phase



OLA
330



OLA
330 COLOR



OLA
500



OLA
500 COLOR



COLOURS



Bianco RAL 9010
White RAL 9010
Blanc RAL 9010



Grigio High Tech RAL 9006
Grey High Tech RAL 9006
Gris High Tech RAL 9006



Grigio antracite RAL 7021
Grey anthracite RAL 7021
Gris anthracite RAL 7021



Corten
Corten
Corten



Bianco RAL 9010 - Rame
White RAL 9010 - Copper
Blanc RAL 9010 - Cuivre peint




Grigio High Tech RAL 9006 - Giallo RAL 1016
Grey High Tech RAL 9006 - Yellow RAL 1016
Gris High Tech RAL 9006 - Jaune RAL 1016



Grigio Antracite RAL 7021 - Oro
Grey anthracite RAL 7021 - Gold
Gris anthracite RAL 7021 - Gold

Ola 330


| IP66 IK 08 5J xx7 CE UK ER | LED | | | COL. | CODE * |
|-------------------------------|-----|------|---------|--|-----------------------------------|
| | W | LM | REAL LM | | |
| | 20 | 2500 | 1200 | <input type="checkbox"/> <input checked="" type="checkbox"/> AC DIRECT | LL144000 <input type="checkbox"/> |



* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Ola 330 Color


| IP66 IK 08 5J xx7 CE UK ER | LED | | | COL. | CODE * |
|-------------------------------|-----|------|---------|--|--|
| | W | LM | REAL LM | | |
| | 20 | 2500 | 1200 | <input type="checkbox"/> <input checked="" type="checkbox"/> AC DIRECT | <input type="checkbox"/> LL14400G <input type="checkbox"/> <input type="checkbox"/> LL14400E <input type="checkbox"/> <input type="checkbox"/> LL14400K <input type="checkbox"/> <input type="checkbox"/> LL14400U <input type="checkbox"/> <input type="checkbox"/> LL14400Y <input type="checkbox"/> <input type="checkbox"/> LL14400Z <input type="checkbox"/> |



* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Ola 500


| IP66 IK 08 5J xx7 CE UK ER | LED | | | COL. | CODE * |
|-------------------------------|-----|------|---------|--|-----------------------------------|
| | W | LM | REAL LM | | |
| | 42 | 5500 | 2139 | <input type="checkbox"/> <input checked="" type="checkbox"/> AC DIRECT | LL144010 <input type="checkbox"/> |



* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Ola 500 Color

| IP66 IK 08 5J xx7 CE UK ER | LED | | | COL. | CODE * |
|-------------------------------|-----|------|---------|--|--|
| | W | LM | REAL LM | | |
| | 42 | 5500 | 2139 | <input type="checkbox"/> <input checked="" type="checkbox"/> AC DIRECT | <input type="checkbox"/> LL14401G <input type="checkbox"/> <input type="checkbox"/> LL14401E <input type="checkbox"/> <input type="checkbox"/> LL14401K <input type="checkbox"/> <input type="checkbox"/> LL14401U <input type="checkbox"/> <input type="checkbox"/> LL14401Y <input type="checkbox"/> <input type="checkbox"/> LL14401Z <input type="checkbox"/> |



* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Accessori | Accessories | Accessoires

Bus DALI

Varialuce universale comandabile con segnale DALI. Dimmerazione a Taglio di Fase discendente (a fine fase) IGBT Trailing-Edge.


| Col. | Code |
|------|-----------|
| - | LB1070110 |

Bus DALI

Universal dimmer controlled by DALI signal. Descending Phase Cutting dimming (at the end of the phase) IGBT Trailing-Edge.

Bus DALI

Variateur universel commandé par un signal DALI. Phase descendante Gradation par coupure (à la fin de la phase) IGBT Trailing-Edge.





FEATURES



Colori disponibili.
Available colours.
Couleurs disponibles.



Versione monocolori.
Single-colour version.
Version monocolori.

Versione bicolore.
Two-colour version.
Version bicolore.





OLA 330 COLOR



OLA 500



