

Stik 60 Opal Bollard 390

LL16121W3

Lombardo.



Informazioni tecniche:

Installazione:	Terra, Paletto/bollard terra
Materiale Corpo:	Alluminio
Finitura:	Bianco RAL 9010
Trattamento:	Bordo Mare
Tipo di diffusore:	Polycarbonato
Tipo lampada:	LED
Classe energetica:	D
Temperatura colore:	3000K
CRI:	>80
LB Factor:	L80B20 - 50.000h
Step MacAdam:	3
Rischio fotobiologico:	RG1
Potenza assorbita Watt:	5,5
Lumen:	800
Real Lumen:	375
Alimentazione:	✓ integrata
LED:	220-240 V
Interruttore magnetotermico	120-/-192-/ B10 - C10 - B16 - C16
Classe di isolamento:	□ CL.II
Cavo Alimentazione:	0,30 metri H05RN-F 2x1
Grado di protezione:	IP 66
Resistenza alla rottura:	IK 09 10J xx7
Marchi di Conformità:	CE UK

Base di fissaggio inclusa.





Stik 60 Opal Bollard 390

Lombardo.

LL16121W3



Immagini di montaggio:



Lombardo S.r.l.

Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - T 0039 035 939 411 - E info@lombardo.it

lombardo.it

LL16121W3

The 3D visualization shows two luminaires mounted on a grid. The grid spacing is 0.5m. The distance between the centers of the two luminaires is 2.5m. The height of the luminaires is 0.39m. A color-coded legend indicates the Lux levels: 50.00 (dark red), 25.00 (red), 10.00 (orange), 5.00 (light orange), and 0.00 (white).