




Stile next 260

DIFF.
OPAL.

IP 66 IK 06 1J xx3 CE UK CEA

LED	W	LM	REAL LM	COL.	CODE *	* LED COLOUR
	10	1300	386	220-240 V	LL785E	4000K 3000K, lm -5%
LAMP	ATT.	LAMP MAX	CFL			
	E27	1x20			LB7852N	



Lampade dim. max: E27 145 mm Ø 48 mm.

Lamp dim. max: E27 145 mm Ø 48 mm.

Lampes dim. max: E27 145 mm Ø 48 mm.

Finishing



* Led colour

- 4000K
- 3000K, lm -5%

Completa il codice
sostituendo al quadrato rosso la lettera o il numero corrispondente alla temperatura colore scelta.

Complete the code
by replacing the red box with the letter or number corresponding to the selected colour temperature.

Compléter le code
en remplaçant le carré rouge par la lettre ou le numéro correspondant à la sélection de température couleur.


✔ Alimentatore integrato

Integrated driver
Alimentation intégrée

ACCESSORI

Accessories / Accessoires

Armatura da incasso Stile 260 Stile Next 260




Armatura da incasso in termoplastico.

Thermoplastic recess box Stile 260 - Stile Next 260
Thermoplastic recess box.

Armature à encastrer Stile 260 / Stile Next 260
Armature à encastrer en matériau thermoplastique.

COL. CODE
LB11530

Cassaforma Polistirolo Stile 260 Stile Next 260



Cassaforma in polistirolo.

Polystyrene mould Stile 260 - Stile Next 260
Polystyrene mould.

Gabarit en polystyrène Stile 260 / Stile Next 260
Gabarit en polystyrène.

COL. CODE
LB11550

Morsettiere
Terminal blocks



Scaricatori SPD
Surge protector devices

