

Trend


Trend 220



DIFF. POLIGLASS

DIFF. TRASP.

POSITION



IP 66 IK 10 20J xx9 CE

LED	W	LM	REAL LM	COL.	CODE **	CODE **	* OPTIC	* LED COLOUR					
A++	15	1900	1170 - 1875			220-240 V							
									LL4911□	LL4941□			
									LL491G□	LL494G□			
									LL491E□	LL494E□			
A++	18	2450	1470 - 2250			220-240 V							
									LL491K□	LL494K□			
									LL490000□	LL490004□			
									LL490001□	LL490005□			
A++	8	860	743			220-240 V							
									LL490002□	LL490006□			
									LL490003□	LL490007□			
									LL4931□□	LL4931□□			
LAMP	ATT.	LAMP MAX	CFL										
									A	E27	1x20	LB49121	LB49421
												LB4912G	LB4942G
												LB4912E	LB4942E
LB4912K	LB4942K												

Versione Monoemissione.
Lampade dim. max: E27 128 mm Ø 48 mm

Unidirectional version.
Lamp max. dim.: E27 128 mm Ø 48 mm.

Version unidirectionnelle.
Lampes dim. max: E27 128 mm Ø 48 mm.


Trend Up&Down 220



DIFF. POLIGLASS

DIFF. TRASP.

POSITION



IP 66 IK 10 20J xx9 CE

LED	W	LM	REAL LM	COL.	CODE **	CODE **	* OPTIC	* LED COLOUR					
A++	15	2200	1260 - 2060			220-240 V							
									LL4921□	LL4951□			
									LL492G□	LL495G□			
									LL492E□	LL495E□			
A++	24	3600	2160 - 3310			220-240 V							
									LL492K□	LL495K□			
									LL490008□	LL490012□			
									LL490009□	LL490013□			
A++	11	1400	1078			220-240 V							
									LL490010□	LL490014□			
									LL490011□	LL490015□			
									LL4961□□	LL4961□□			
LAMP	ATT.	LAMP MAX	CFL										
									A	E27	1x20	LB49221	LB49521
												LB4922G	LB4952G
												LB4922E	LB4952E
LB4922K	LB4952K												

Versione Biemissione.
Lampade dim. max: E27 128 mm Ø 48 mm.

Bidirectional version.
Lamp max. dim.: E27 128 mm Ø 48 mm.

Version bidirectionnelle.
Lampes dim. max: E27 128 mm Ø 48 mm.

Finishing

	Bianco RAL 9010 White RAL 9010 Blanc RAL 9010		Grigio antracite RAL 7021 Grey anthracite RAL 7021 Gris anthracite RAL 7021
	Grigio High Tech RAL 9006 Grey High Tech RAL 9006 Gris High Tech RAL 9006		Corten Corten Corten

Alimentazione diretta

Integral ballast
Alimentation intégrée

220-240 V