

Stile next 106L asimmetrica

IP 66 IK 06 1J xx3 CE

Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100.

Double cable entries at the back.
Reflector made of EN-AB44100 die-cast aluminium primary alloy.

Possibilit  alimentazione double entr e. R flecteur en aluminium primaire inject  EN-AB44100.



LED
310 lm 3W
real output lm 38



Specif.

CL.I E

Col.


Vetro/Glass

LL664C

led colour

N = (4000K)

3 = (3000K, lm -5%)



172x68 mm
6 3/4" x 2 5/8"

Stile next 106L asimmetrica orizzontale

IP 66 IK 06 1J xx3 CE

Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100.

Double cable entry at the back.
Reflector made of EN-AB44100 die-cast aluminium primary alloy.

Possibilit  alimentazione double entr e. R flecteur en aluminium primaire inject  EN-AB44100.



LED
490 lm 4W
real output lm 70



Specif.

CL.I E

Col.


Vetro/Glass

LL666F

led colour

N = (4000K)

3 = (3000K, lm -5%)



172x68 mm
6 3/4" x 2 5/8"

